





330 VOLARE DIRETTA SYSTEM

2 - Phasen Stromschiene
2 - Circuit rail track
Binario a 2 fasi
Rail bi-phasé




2 - Phasenschiene mit Bohrungen und Befestigungsmaterial; 230V; max. Belastung: 10A pro Phase; beliebig kürzbar


2 - Circuit rail track incl. holes and mounting parts; 230V max. load: 10A per phase; can be cut to any length


Binario a 2 fasi; perforato, con materiale per il montaggio; 230V, accorciabile

Rail bi-phasé 230V; avec trous et matériel de montage; longueur ajustable

IP 20   

21-11135d  L: 1000mm

21-11235d  L: 2000mm

21-11335d  L: 3000mm

21-10131d  L: 1000mm


21-10231d  L: 2000mm

21-10135d  L: 1000mm

21-10235d  L: 2000mm





21-10335d  L: 3000mm

Alle Stromschiene
müssen mit einer End-
kappe versehen werden!



All track endings have
to be equipped with
endpieces!

Ogni estremità deve
essere completata
con testata di chi-
usura!


- 21-10034 
- 21-10035 
- 21-10036 
- 21-10037 

Chaque extrémité doit
être fermée avec un
embout!




Endeinspeisung



End power feed




Alimentazione all'estremità


- 21-41040 
- 21-410401 
- 21-410405 

Alimentation en ext-
remite




Mitteleinspeisung



Center power feed



Alimentazione cen-
trale


- 21-41041 
- 21-410411 
- 21-410415 

Alimentation centrale



Kabeleinspeisung mit
Baldachin; beliebig
kürzbar



Cable power feed with
canopy; can be cut to
any length



Alimentazione a cavo
con basetta, accor-
ciabile


- 21-44035  L: 1000mm; 5 x 1,5mm²
- 21-44045  L: 1500mm; 5 x 1,5mm²

Alimentation a câble
et base; longueur
ajustable

Kabel Endeinspeisung;
beliebig kürzbar, ohne
Baldachin



Cable end power feed;
can be cut to any
length, without canopy



Cavo di alimentazione
per estremità, accor-
ciabile


- 21-41035  L: 2000mm; 5 x 1,5mm²
- 21-41031  L: 2000mm; 5 x 1,5mm²
- 21-41032  L: 2000mm; 5 x 1,5mm²

Alimentation à câble;
longueur ajustable


Kabel Endeinspeisung;
beliebig kürzbar, mit
Baldachin



Cable end power feed;
can be cut to any
length, with canopy



Cavo di alimentazione
per estremità, accor-
ciabile


- 21-41055  L: 2000mm; 5 x 1,5mm²
- 21-41051  L: 2000mm; 5 x 1,5mm²
- 21-41052  L: 2000mm; 5 x 1,5mm²

Alimentation à câble;
longueur ajustable




Mitteleinspeisung
beliebig kürzbar, mit
Baldachin



Center power feed, can
be cut to any length,
with canopy



Alimentazione centra-
le, accorciabile


- 21-44055  L: 1000mm; 5 x 1,5mm²
- 21-44051  L: 1000mm; 5 x 1,5mm²
- 21-44052  L: 1000mm; 5 x 1,5mm²

Alimentation centrale;
longueur ajustable

Linearverbinder



Linear junction



Giunto lineare


21-30035  L: 70mm; 4 x 1,5mm²

Jonction linéaire

Flexibler Winkelver-
binder



Flexible junction



Giunto flessibile


21-31035  L: 110mm; 4 x 1,5mm²

Jonction flexible




90° Winkelverbinder



90° junction



Giunto a 90°


- 21-32035  L: 25mm; 4 x 1,5mm²
- 21-32031  L: 25mm; 4 x 1,5mm²
- 21-32032  L: 25mm; 4 x 1,5mm²

Jonction à 90°



Isolierverbinder



Insulating junction



Giunto isolante


- 21-30135  L: 70mm; 4 x 1,5mm²
- 21-30132  L: 70mm; 4 x 1,5mm²

Jonction isolante




T-Verbinder



T-junction



T-Giunto


- 21-30036  L: 130 x B: 65mm ; 4 x 1,5mm²
- 21-30038  L: 130 x B: 65mm; 4 x 1,5mm²
- 21-30040  L: 130 x B: 65mm; 4 x 1,5mm²

T-Jonction




Kreuzverbinder



Cross-junction



Crociata -giunto

- 21-30037  L: 130 x B: 130mm ; 4 x 1,5mm²
- 21-30039  L: 130 x B: 130mm; 4 x 1,5mm²
- 21-30041  L: 130 x B: 130mm; 4 x 1,5mm²

Croix-Jonction

Seilabhängung



Steel cord suspension

Sospensione

- 21-160608  L: 1000mm
- 21-160601  L: 1000mm
- 21-160605  L: 1000mm




Suspension

Deckenbefestigung






Ceiling bracket

Fissaggio soffitto

- 21-160538  H: 71mm
- 21-160531  H: 71mm
- 21-160535  H: 71mm

Fixation plafond

- 21-160438  H: 15mm
- 21-160431  H: 15mm
- 21-160435  H: 15mm

Folgende Strahler und Leuchten von Molto Luce sind
mit dem VOLARE DIRETTA Schienensystem kompatibel:

The following luminaires and lamps of Molto Luce are
compatible with our VOLARE DIRETTA rail system:

STRATO
CONTE
ELOS
BASSO
ROCCO
SENSO
CAROH
TANDEM
CULTO XS
C-YOU XS
SHOOTER
SHOOTER LED
MIX
NINA
NINI
VOLTO
VOLTO COPERTO
RETTA

Nähere Informationen / More information:
www.moltoluce.com

